

ZPB 2980

ENERGY STORAGE SYSTEM



TECHNICAL SPECIFICATIONS

MODEL	IA-1488KW/2980KWH-DA10	IA-1302 KW/2600KWH-DA10	IA-1116 KW/2230KWH-DA10	IA-930 KW/1860KWH-DA10	IA-744 KW/1490KWH-DA10	IA-744 KW/2980 KWH-DA10
Battery						
Battery Type	LFP , 3.2 V / 280 Ah					
Battery PACK Configuration	1P*52S					
Battery Capacity	2981 kWh (46.59 kWh * 8 * 8)	2609 kWh (46.59 kWh * 8 * 7)	2236 kWh (46.59 kWh * 8 * 6)	1863 kWh (46.59 kWh * 8 * 5)	1490 kWh (46.59 kWh * 8 * 4)	2981 kWh (46.59 kWh * 8 * 8)
Rated Battery Voltage / Voltage Range	1331.2 V / 1164.8...1497.6 V					
Max. Charging/ Discharging Current	140 A*8	140 A*7	140 A*6	140 A*5	140 A*4	140 A*4
Max. Charging/ Discharging Power	1456 kW /1528 kW	1274 kW /1337 kW	1092 kW / 1146 kW	910 kW / 955 kW	728 kW / 764 kW	728 kW / 764 kW
AC Parameters (On-grid)						
Rated Output Power	186 kW*8	186 kW*7	186 kW*6	186 kW*5	186 kW*4	186 kW*4
Rated Voltage	3W+PE, 690 V					
Voltage Range	587...759 V					
Rated Output Current	1245 A	1089 A	933 A	778 A	622 A	622 A
Rated Frequency	50/60 Hz					
Total Harmonic Distortion (THDi)	< 3%					
Power Factor	-1...+1					
General Data						
Dimensions (W*D*H)	6058*2438*2896 mm					
Weight	~ 32 t	~ 28.4 t	~ 24.8 t	~ 21.2 t	~ 17.6 t	~ 32 t

TECHNICAL SPECIFICATIONS

General Data	
Operating Temperature Range	-25°C...+60°C (derating @ > 50°C)
Relative Humidity	0...95% (Non-condensing)
Altitude	≤ 3000 m (derating @ > 2000 m)
Cooling	Smart Air Cooling (PCS) Liquid Cooling (Battery)
Noise	< 75 dB
Ingress Protection	IP55
Firefighting	Smoke Detector, Heat Detector, Alarm Sounder, Aersol, Sprinkler, Flammable Gas Detector, Vent Plate
Communication	Ethernet
Installation	Floor-standing
Standard ¹	IEC62619, IEC63056, IEC62477, IEC61000, UN38.3, EN50549-1, EN50549-2, EN50549-10

Specifications provided are preliminary and subject to change.